



Special Transport Trolleys ▶ ▶ For heavy loads up to 40 t

GKS-PERFEKT Swing Trolley Set F6-p/L6-p

- Suitable for uneven floors. Up to 12 t load capacity
- Wheels are bedded in a rocker, that allows a swinging of $\pm 10^\circ$
- Other load capacities upon request

Container Trolley Set with Twistlock System

- Tandem trolley set with 4-point support for quick and secure connecting of trolleys with ISO-Containers
- For load capacities up to 12 t, 24 t or 40 t



F6-p/L6-p

Container Trolley Set F12-c/TL12-c

Technical data	F6-p	L6-p	F6-c	TL6-c	F12-c	TL12-c	F20-c	TL20-c
Item number	13041	13046	13642	13643	14130	14129	13293	13294
Load capacity	60 kN (6 t)	60 kN (6 t)	60 kN (6 t)	60 kN (6 t)	120 kN (12 t)	120 kN (12 t)	200 kN (20 t)	200 kN (20 t)
Loading height	110 mm	110 mm	176 mm	176 mm	176 mm	176 mm	225 mm	225 mm
No. of Wheels (Dim.)	8 (85 x 85 mm)	8 (85 x 85 mm)	8 (85 x 85 mm)	8 (85 x 85 mm)	16 (85 x 85 mm)	16 (85 x 85 mm)	8 (140 x 85 mm)	8 (140 x 85 mm)
Contact surface	235 x 272 mm	Ø 170 mm	-	-	-	-	-	-
Overall dimensions (L x W)	-	576 x 765 mm	-	*x 2259 mm	-	*x 2259 mm	-	*x 2259 mm
Weaving	$\pm 10^\circ$	$\pm 10^\circ$	-	-	-	-	-	-
Tare weight ca.	33 kg	45 kg	50 kg	75 kg	61 kg	155 kg	140 kg	280 kg
Total load capacity	120 kN (12 t)		120 kN (12 t)		240 kN (24 t)		400 kN (40 t)	

Technical specifications are subject to change

*Length and width acc. to container dimensions (10 ft, 20 ft, 40 ft,...)