

HOSES

Internal diameter: 6.3 and 9.7 mm
 Length: 0.6 - 20 m
 Maximum operating pressure: 700 bar

Hoses

- Flexible tubes of 1/4" - internal Ø of 6.3 mm, operating pressure 700 bar.
- For demanding applications with a 4:1 safety factor.
- Also available in custom sizes and types.

Hoses with internal Ø of 10 mm for applications with high flows or with very long hoses also available.



MODEL	HOSE AND QUICK COUPLERS ASSEMBLY		LENGTH m
	END 1	END 2	
TFR - 0.6	3/8" NPT	3/8" NPT	0.6
TFR - 1	3/8" NPT	3/8" NPT	1
TFR - 2	3/8" NPT	3/8" NPT	2
TFR - 3	3/8" NPT	3/8" NPT	3
TFR - 4	3/8" NPT	3/8" NPT	4
TFR - 5	3/8" NPT	3/8" NPT	5
TFR - 6	3/8" NPT	3/8" NPT	6
TFR - 10	3/8" NPT	3/8" NPT	10
TFRR - 0.6	1/4" NPT	1/4" NPT	0.6
TFRR - 1	1/4" NPT	1/4" NPT	1
TFRR - 2	1/4" NPT	1/4" NPT	2
TFRR - 3	1/4" NPT	1/4" NPT	3
TFRR - 4	1/4" NPT	1/4" NPT	4
TFRR - 5	1/4" NPT	1/4" NPT	5
TFRR - 6	1/4" NPT	1/4" NPT	6
TFRR - 10	1/4" NPT	1/4" NPT	10
TFG - 0.6	3/8" NPT	GR - 6M	0.6
TFG - 1	3/8" NPT	GR - 6M	1
TFG - 2	3/8" NPT	GR - 6M	2
TFG - 3	3/8" NPT	GR - 6M	3
TFG - 4	3/8" NPT	GR - 6M	4
TFG - 5	3/8" NPT	GR - 6M	5
TFG - 6	3/8" NPT	GR - 6M	6
TFG - 10	3/8" NPT	GR - 6M	10
TFGG - 0.6	GR - 6M	GR - 6M	0.6
TFGG - 1	GR - 6M	GR - 6M	1
TFGG - 2	GR - 6M	GR - 6M	2
TFGG - 3	GR - 6M	GR - 6M	3
TFGG - 4	GR - 6M	GR - 6M	4
TFGG - 5	GR - 6M	GR - 6M	5
TFGG - 6	GR - 6M	GR - 6M	6
TFGG - 10	GR - 6M	GR - 6M	10

TFR**TFRR****TFG****TFGG**